



Soudal Surface Booster

Product description

Soudal Surface Booster is a highly effective, fast acting, aerosol, cleaning and degreasing agent. Soudal Surface Booster promotes adhesion of adhesive and sealants on non-porous substrates.

Properties

- Cleans and degreases
- Promotes adhesion of adhesives, sealants, foams, ...
- Increases life time of sealant adhesion
- Multi-purpose use
- Leaves no residue
- Fast drying
- Fast acting
- Ready to use
- Non-abrasive

Applications

- Substrate preparation before sealing and adhering.
- Suitable for cleaning and degreasing mechanical parts.
- Removal of uncured MS, PU, silicone sealants, tar residue, grease, wax,...

Technical data

Base	Solvent mixture
Consistency	Liquid
Density	Ca. 0.8 g/ml
Application temperature	+5°C → +35°C
Flashpoint	Ca. 10 °C
Volatile organic compounds (VOC)	Ca. 100%

Substrates

- Substrate types
Substrates: All non-porous substrates. We recommend a preliminary compatibility test on every surface.

Application method

- Application method
Shake can well before use. Spray at a distance of approx. 20 cm of the object. Apply as required. After applying rub the surface dry with a clean towel. Always rub in one direction. Test for adverse effects on the surface in advance.

Health- and Safety Recommendations

Take the usual labour hygiene into account. Consult label and safety data sheet for more information.

Use only in well-ventilated areas.

In case of contact with eyes, wash immediately with plenty of water.

Dangerous. Respect the precautions for use.



Soudal Surface Booster

Packaging/Logistics

Shelf life: 3 years in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C

Remarks

- Due to the wide variety of possible plastics and paints and to avoid damage to the surface, a preliminary compatibility test is recommended.
- Do not use in double glazing applications
- Do not use in direct sunlight.
- Do not store in direct sunlight.

This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. It is general in nature and does not constitute any liability. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application. In every case it is recommended to carry out preliminary experiments. The manufacturer reserves the right to modify products without prior notice.