



Soudal Prep'Air

Product description

Soudal Prep'Air is a high pressure gas spray, developed for cleaning and dedusting porous and non-porous substrates.

Properties

- Cleans and dedusts
- Promotes adhesion of adhesives, sealants, foams, ...
- Increases life time of sealant adhesion
- Leaves no residue
- Fast acting
- Ready to use
- Non-abrasive

Applications

- Removal of dirt and dust from joint substrates.
- Dedusting drill hules
- Handsfree removal of cobwebs, dirt, dust, sawdust, loose rust, metal flakes, ...

Technical data

Base	Gaseous mixture
Consistency	Gaseous
Density	Ca. 0.001 g/ml
Application temperature	-10°C → +35°C

Substrates

- Substrate types
Substrates: All substrates. We recommend a preliminary compatibility test on every surface.

Application method

- Application method
Do not shake the can before use. Spray at a distance of approx. 3 cm of the surface until completely dirt and dust free.

Health- and Safety Recommendations

Take the usual labour hygiene into account. Consult label and safety data sheet for more information.

Packaging/Logistics

Shelf life: 3 years in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C

Environmental clauses

- Leed regulation: the product conforms to the requirements of LEED. Low -Emitting Materials: Adhesives and Sealants. SCAQMD rule 1168. Complies with USGBC LEED 2009 Credit 4.1: Low-Emitting Materials – Adhesives & Sealants concerning the VOC-content.

Remarks

- Do not store in direct sunlight.



Soudal Prep'Air

This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. It is general in nature and does not constitute any liability. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application. In every case it is recommended to carry out preliminary experiments. The manufacturer reserves the right to modify products without prior notice.