

DECLARATION OF PERFORMANCE

LEXAN™ THERMOCLEAR™ SHEET
LT2UV169X

1.
Element allowing identification of the construction product:
LT2UV169X

2.
Intended use:
For internal and external use in roofs, walls, and ceilings.

3.
Manufacturer:
F&S B.V.
Plasticslaan 1
4612 PX Bergen op Zoom
Netherlands

4.
System of Assessment and Verification of Constancy of Performance (AVCP):
AVCP System 3 for all characteristics.

5.
In case of the declaration of performance concerning a construction product covered by a harmonized standard:
WFRGENT (Notified Body 1173), performed testing of the reaction to fire (based on sampling carried out by the manufacturer) under system 3.

6.
Declared performance:
All characteristics listed in the table below are determined following harmonized standard EN 16153: 2013+A1:2015 Light transmitting flat multiwall polycarbonate (PC) sheets for internal and external use in roofs, walls, and ceilings.

DECLARATION OF PERFORMANCE

7. Element allowing identification of the construction product:

Essential characteristics	Performance		
External fire performance	F _{ROOF} (NPD)		
Reaction to fire	B, s1, d0		
Resistance to fire	NPD		
Water vapor permeability	3,8 ´ 10 ⁻⁵ mg/m×h×Pa		
Water/air permeability	Pass		
Release of dangerous substances	NPD		
Dimensional tolerances	Pass		
Shatter properties (safe breakability) as:			
- Small hard body impact resistance	Pass		
- Large soft body impact resistance (assembly)	Pass		
Deformation behavior	B _x = 142 Nm ² /m		
	B _y = 101 Nm ² /m		
	S _y = 14068 N/m		
	M _b = 29 Nm/m		
Direct airborne sound insulation	R = 18 dB		
Thermal transmittance	U = 1.77 W/m ² K		
Light transmittance	τ _v		
Color	112	WH7A092X	515055
τ _v (%)	49	NPD	30
Resistance to fixings	Method of fixing (see manufacturer's datasheet)		
Durability, as variation (after ageing 20Y):			
- of yellowness index	6 (ΔA) Clear 10 (ΔA) Colored		
- of the light transmittance	8%		
- of deformation flexural modulus	Cu 1		
-of tensile strength	Ku 1		

8. The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

P. van den Bleek

Bergen op Zoom, 01-09-2024



POLYVANTIS

Joulehof 16
4622 RG Bergen op Zoom
The Netherlands
E lexan.info@polyvantis.com
www.polyvantis.com

